Change block size 512e <-> 4kn with Niagara Customer Edition

- 1. Launch Niagara (SPTI) Device Rescan Format
- 2. If a drive is listed in grey colour unlock the drive with Lock Drive

🍯 Niagara Customer Edition (uil=spti, suil=serial) – 🗖 💌			- 🗆 🗙
Niagara			<u>+</u> 8
Device List 0: spti Device Rescan Synchronize Console/GUI Cobra-F-4K 08V10VGH Dev: 91 Array HISST HUSSZONMOAL Unitmover Dev	Powered by The Firmware Te SCSI ATA NVM SCSI Commands CDB ▼ Change_definition close_zone e6 finish_zone format_unit inquiry io10 io12 io16 io32 io6 log_select log_sense SCSI Tools	est & Tools Team e Standard Cmds Inquiry Start Unit Stop Unit Test Ready	Frequent Cmds
< <p>Niagara Options Lock Drives Tools & Cmds Niagara Window Xiagara 3,</p>	SSD Tools ▼ Buffer Manager Drive Fitness Test Error Inject Eye Diagram LBA Conversion Mode Parms Quick run SSD Assert Decoder Super CSO v1 TCG Setup Temperature Timestamp Entry 4.6.0 © 2015 HGST, a Western Digita	Standard Tools Download Code Format Go No Go LogDump Mem Dump Mode Fields SuperCSO I company	Frequent Tools Defect List Drive Fitness T

- Untick Fast Format Set to 512e Format 3. Format 4kn drive to 512e: (see page 2) 4. Format 51e drive to 4kn: Untick Fast Format - Set to 4K – Format (see page 3)



Format 4kn drive to 512e: Untick Fast Format - Set to 512e - Format



Format 512e drive to 4kn: Untick Fast Format - Set to 4K - Format