



Dolby Digital Decoder

DVD-Video, DVD-R, DVD-RW (video mode), DVD+R, DVD+RW, Audio CD, Video CD, Super Video CD, CD-R, CD-RW, MP3 CVBS, RGB, S-Video, 2 x SCART output

5 record modes (quality):

HQ=1h; SP=2h; LP=3h; EP=4h; EP+=6h



CH-DVR 750

General specifications

Playable disc types: DVD-Video, DVD-R, DVD-RW (video mode), DVD+R, DVD+RW, Audio CD, Video CD, Super Video CD, CD-R, CD-RW, MP3

TV systems supported: NTSC, PAL

Video out formats: CVBS, RGB, S-Video

Video in formats: CVBS, S-Video, DV in

Power supply: AC 100~230V, 50/60Hz

Power consumption: 28W

Power consumption (standby): 7W (clock display on), 3W (clock display off)

Dimensions (W x H x D): 430mm x 65mm x 345mm (disc tray closed), 479mm (disc tray opened)

Weight without packaging approx.: 4.4 kg

Power outage/no power: channel- and timer information remain saved for up to 1 year, the time is saved for up to 4 hours.

Operation status: Horizontal

Operation conditions: 5°C to 35°C (41°F to 95°F)

Humidity: 25% - 75%

Front connections:

S-Video input: Hosiden 4-pin, Composite-Video input: Cinch (yellow)

Analogue audio input: Cinch (white/red), DV input: IEEE 1394 4-pin

Audio features: D/A converter: 24 bit / 96 kHz, A/D converter: 16 bit

Frequency response: DVD (96 kHz): 4 Hz to 44 kHz, DVD (48 kHz): 4 Hz to 22 kHz

CD/Video CD (44.1 kHz): 4 Hz to 20 kHz

Signal-to-noise ratio: 95 dB

Dynamic range: 85 dB

Harmonic distortion: 95 dB

Rear connections

AV SCART out (EXT1): 0.7Vpp (75 ohm)

AV SCART in (EXT2): 0.7Vpp (75 ohm)

S-Video out: Hosiden 4-pin, (Y) 1Vpp (75 ohm), (C) 0.3Vpp (75 ohm)

Composite-Video out: Cinch (yellow), 1Vpp (75 ohm)

Analogue Audio out: Cinch (white/red)

Digital Audio out: Coaxial

RF antenna in: Coaxial 75 ohm (IEC type)

RF TV out: Coaxial 75 ohm (IEC type)

RECORD

