




# MultiSpin 40Xi (CDR-3001)



- 17-40X CAV drive with MPSS (Maximum Performance Spinning System) technology
- internal 12/8cm CD-ROM disc drive (half height form factor)
- IDE/ATAPI interface with UltraDMA33 (max. 33 MByte/sec transfer rate)
- Tray load mechanism supporting horizontal and vertical use
- dust protected enclosure
- emergency eject
- CD-RW read capability
- analog- and digital audio output connector




Specifications	MultiSpin 40Xi
Data Transfer Rate	2550-6000 kByte/s
Access Time	85 ms
Cache Memory	128 kByte
Mechanism	motorized Tray load mechanism for horizontal and vertical use
Interface	IDE / ATAPI
Burst Transfer Rate	PIO mode 4 / Ultra-DMA 33
Audio	headphone jack and volume control at front plus digital-out and line-out (MPC compatible) at the back
Compatibility	High Sierra, ISO9660, CD-Audio, CD-ROM (mode1 and mode 2), CD-ROM XA, Single- and MultiSession Kodak Photo CD, CD-I (FMV), Video CD, Enhanced Music CD (CD+), CD TEXT, MPC Level 3, CD-RW read (in compliance with MultiRead spec.), PC99
Weight	0.93 kg
Dimensions	149mm x 42,8mm x 208mm

Designed for  
  
 Microsoft  
 Windows NT  
 Windows 98

  
 MPC3  
 Multimedia PC

  
 MultiRead

  
 enhanced CD

  
 COMPACT  
 disc  
 DIGITAL VIDEO

**NEC MultiSpin CD-ROM Drives**

**NEC**  
 NEC Europe Ltd.