

NEC MultiSync® FE750

CRT Type:	43 cm (17 inch) Flat face aperture grille CRT 90° deflection
Active Screen Size:	41 cm
Anti-Reflection System:	OptiClear™ coating
Active Display Area*:	325 x 244 mm (Full scan)
Grille Pitch:	0.25 mm
Horizontal Frequency:	31–92 kHz
Vertical Frequency:	55–160 Hz
Maximum Resolution:	1600 x 1200 @ 73 Hz
Recommended Resolution:	1024 x 768 @ 85 Hz (VESA recommendation)
Other Resolutions:	1280 x 1024 @ 85 Hz, 1152 x 870 @ 99 Hz, 1024 x 768 @ 112 Hz, 832 x 624 @ 135 Hz, 800 x 600 @ 140 Hz, 640 x 480 @ 160 Hz
Features/Adjust Functions:	Plug & Play (DDC1 + DDC2B) for Windows 95/98, Asset Management, On-Screen Manager (OSM) lock out, Contrast, Brightness, Geometry, Rotation, Color control, Horizontal and vertical static and dynamic convergence control, Corner correction, Moiré cancellation, Auto adjust, Refresh notification, Monitor info, Language select, Intelligent Power Management (VESA/EPA/NUTEK compliant) disable
Safety/Ergonomics:	CE, TÜV GS, TÜV ERGONOMIE, ISO 9241-3/-7/-8, TCO99
Dimensions (W x H x D):	403 x 427 x 424 mm
Weight:	20.0 kg
Power Supply:	100–120 V/220–240 V, 50–60 Hz
Power Requirements:	95 W typ. on mode, ≤ 15 W suspend mode, ≤ 5 W sleep mode
Connection:	Mini 15 pin D-sub 1.8 m signal cable
Warranty:	3 years warranty, warranty extension programs depending on specific country
Shipping Contents:	Monitor, Power cord, User manual
Optional Accessories:	Apple Macintosh Adapter

All specifications are subject to change without notice. Status February 2000

* Depending on signal of graphics card

- Natural Flat CRT for absolutely flat image
- Digital convergence control for sharp image including the corners
- Extended control features for a perfect image
- Monitor data manageable over networks due to Asset Management feature
- Ergonomics and safety compliant to state of the art standards



NEC Deutschland GmbH
Steinheilstr. 4–6
85737 Ismaning
Germany

Phone:
+49-89-9 6274-0

Web site:
www.necd.de

NEC
One idea ahead.