

NEC MultiSync® FE950

CRT Type:	49.5 cm (19 inch) Flat face aperture grille CRT 90° deflection
Active Screen Size:	45.8 cm (18")
Anti-Reflection System:	OptiClear™ coating
Active Display Area*:	366 x 275 mm (Full scan)
Grille Pitch:	0.25–0.27 mm
Horizontal Frequency:	31–96 kHz
Vertical Frequency:	55–160 Hz
Maximum Resolution:	1600 x 1200 @ 77 Hz
Recommended Resolution:	1280 x 1024 @ 85 Hz (VESA recommendation)
Other Resolutions:	1280 x 1024 @ 89 Hz, 1152 x 870 @ 105 Hz, 1024 x 768 @ 120 Hz, 832 x 624 @ 144 Hz, 800 x 600 @ 152 Hz, 640 x 480 @ 160 Hz
Features/Adjust Functions:	Plug & Play (DDC1 + DDC2B) for Windows 95/98, Asset Management, On-Screen Manager (OSM) lock out, Contrast, Brightness, Geometry, Rotation, Color Control, Horizontal and vertical static and dynamic convergence control, corner correction, Moiré cancellation, Auto adjust, GlobalSync®, Refresh notification, Monitor info, Language select, Intelligent Power Management (VESA/EPA/NUTEK compliant) disable
Safety/Ergonomics:	CE, TÜV GS, TÜV ERGONOMIE, ISO 9241-3/-7/-8, TCO 99
Dimensions (W x H x D):	442 x 456 x 447 mm
Weight:	24.5 kg
Power Supply:	100–120 V/220–240 V, 50–60 Hz
Power Requirements:	100 W typ. on mode, ≤ 15 W suspend mode, ≤ 5 W sleep mode
Connection:	Mini 15 pin D-sub 1.8 m signal cable
Warranty:	3 years warranty, warranty extension programs depending on specific country
Shipping Contents:	Monitor, Power cord, User manual

All specifications are subject to change without notice. Status February 2000

* Depending on signal of graphics card

- Natural Flat CRT for absolutely flat image
- Digital convergence control for sharp image including the corners
- Extended control features for a perfect image
- Monitor data manageable over networks due to Asset Management feature
- Ergonomics and safety compliant to state of the art standards



NEC Deutschland GmbH
Steinheilstr. 4–6
85737 Ismaning
Germany

Phone:
+49-89-9 6274-0

Web site:
www.necd.de

NEC
One idea ahead.