NEC MultiSync® FP1350

CRT Type:	55.3 cm (22 inch) Flat face aperture grille CRT
Active Screen Size:	50.8 cm
Anti-Reflection System:	OptiClear™ coating
Active Display Area*:	406 x 305 mm (Full scan)
Grille Pitch:	0.25–0.27 mm
	31–115 kHz
Horizontal Frequency:	55–160 Hz
Vertical Frequency: Maximum Resolution:	1920 x 1440 @ 76 Hz
Recommended Resolution:	1600 x 1200 @ 85 Hz (VESA recommendation)
Other Resolutions:	1600 x 1200 @ 92 Hz, 1280 x 1024 @ 107 Hz, 1024 x 768 @ 143 Hz,
	800 x 600 @ 160 Hz, 640 x 480 @ 160 Hz, all Apple resolutions
Features/Adjust Functions:	Plug & Play (DDC1 + DDC2B) for Windows 95/98, Asset Management,
	On-Screen Manager (OSM) lock out, OSM position, Contrast, Brightness,
	Geometry, Rotation, Colour control, Horizontal and vertical static and
	dynamic convergence control, Corner correction, Moiré cancellation,
	Auto adjust, GlobalSync [®] , Refresh notification, Monitor info, Language
	select, Sharpness, Edge lock, Intelligent Power Management (VESA/
	EPA/NUTEK compliant) disable
Safety/Ergonomics:	CE, TÜV GS, TÜV ERGONOMIE, ISO 9241-3/-7/-8, TCO 99
Dimensions (W x H x D):	483 x 501 x 472 mm
Weight:	34 kg
Power Supply:	100–120 V/220–240 V, 50–60 Hz, 2.3 A/1.0 A
Power Requirements:	160 W typ. on mode, \leq 15 W suspend mode, \leq 5 W sleep mode
Connection:	Mini D-sub 15 pin, 5 x BNC (Sync on green) switchable
Warranty:	3 years warranty, warranty extension programs depending on
	specific country
Shipping Contents:	Monitor, Power cord, Mini D-Sub signal cable 1.8 m, CD-ROM with
	USB control software, User manual
Optional Accessories:	Apple Macintosh adapter
All specifications are subject to change witho	ut notice. Status February 2000 * Depending on signal of graphics card

- Natural Flat CRT for absolutely flat image
- Digital convergence control for sharp image including the corners
- Extended control features for a perfect image
- Monitor data manageable over networks due to Asset Management feature
- USB control input
- · Ergonomics and safety compliant to state of the art standards







NEC Deutschland GmbH Steinheilstr. 4–6 85737 Ismaning Germany

Phone: +49-89-96274-0

Web site: www.necd.de

