

NEC MultiSync® LCD1525S


Display Type:	Active Matrix Analogue TFT, 15.4 inch
Active Display Area:	305 x 244 mm
Pixel Pitch:	0.239 x 0.239 mm
Viewing Angle:	120° horizontal/95° vertical (at CR = 10:1)*
Brightness:	200 cd/m ² typ.
Contrast Ratio:	200:1 typ.
Number of Colours:	Unlimited
Optimum Resolutions:	1280 x 1024 @ 60 Hz
Other Resolutions:	1024 x 768, 800 x 600, 720 x 400, 720 x 400, 720 x 350, 640 x 480, 640 x 400, 640 x 350
Features/Adjust Functions:	On-Screen Manager (OSM) lock out, Contrast, Brightness, Auto adjust, Fine adjust, Colour control, Monitor info, Language select, Intelligent Power Management (VESA/EPA/NUTEK compliant) disable
User Controls:	On/Off, OSM Menu, Interfaces
Plug & Play, Asset Management:	VESA DDC1, DDC2B and EDID standard**
Horizontal Frequency:	24–80 kHz
Vertical Frequency:	56–76 Hz
Input Connector:	2 x Mini D-sub 15 pin
Audio Functions:	No
USB Functions:	Yes, active USB hub, 2 x upstream, 4 x downstream
VESA Mounting Interface:	Yes, 75 x 75 mm
Kensington Lock:	Yes
Dimensions (W x H x D):	370 x 360 x 158 mm
Screen Tilt/Rotate:	-5° to +30° / -45° to +45°
Weight:	5.0 kg
Power Supply:	100–240 V, 0.8/0.5 A, integrated power supply
Power Requirements:	58 W max. On mode, < 5 W Power saving mode (Display)
Ambient Temperature (Operat.):	+5 °C to +35 °C
Ambient Humidity (Operating):	30–80 % (non-condensing)
Safety/Ergonomics:	CE, TÜV GS, TÜV ERGONOMIE, ISO 9241-3/-7/-8, TCO 99
Warranty:	3 years warranty, warranty extension programs depending on specific country
Shipping Contents:	Monitor, Power cord, VGA signal cable 1.8 m, USB cable, User manual
Optional Accessories:	Apple Macintosh adapter

All specifications are subject to change without notice. Status February 2000

* CR = Contrast Ratio. All viewing angle specification is based on a contrast ratio of 10:1. Some manufacturers specify viewing angle at a contrast ratio of 5:1 which implies a very pale image.

** Most actual INF file for automatic adaption into Windows 95/98 is downloadable from: www.necd.de

- Professional LCD monitor with analogue TFT panel
- New compact design with 1280 x 1024 resolution
- Active USB hub with 2 x upstream and 4 x downstream connectors
- Two analogue VGA inputs
- VESA mounting interface provides versatile installation
- Ergonomics and safety compliant to state of the art standards



NEC Deutschland GmbH
Steinheilstr. 4–6
85737 Ismaning
Germany

Phone:
+49-89-9 6274-0

Web site:
www.necd.de

NEC
One idea ahead.