

NEC MultiSync® LCD1525V

| | |
|--------------------------------|--|
| Display Type: | TFT Active Matrix Color LCD, 15.1 inch |
| Active Display Area: | 307 x 230 mm |
| Pixel Pitch: | 0.30 x 0.30 mm |
| Viewing Angle: | 110° horizontal/80° vertical (at CR ≥ 10:1)* |
| Brightness: | 200 cd/m ² typ. |
| Contrast Ratio: | 200:1 typ. |
| Number of Colours: | 16.19 million with Colour Smoothing Control |
| Optimum Resolutions: | 1024 x 768 @ 60 Hz |
| Other Resolutions: | 832 x 624, 800 x 600, 720 x 400, 720 x 400, 720 x 350, 640 x 480, 640 x 400, 640 x 350 |
| Features/Adjust Functions: | On-Screen Manager (OSM) lock out, Contrast, Brightness, Auto adjust, Fine adjust, Colour control, Monitor info, Language select, Position, Size, Intelligent Power Management (VESA/EPA/NUTEK compliant) disable |
| User Controls: | On/Off, OSM Menu |
| Plug & Play, Asset Management: | VESA DDC1, DDC2B and EDID standard** |
| Horizontal Frequency: | 24.8–48.4 kHz |
| Vertical Frequency: | 56.2–75 Hz |
| Input Connector: | Mini D-sub 15 pin |
| Audio Functions: | No |
| USB Functions: | No |
| VESA Mounting Interface: | Yes, 75 x 75 mm |
| Kensington Lock: | Yes |
| Dimensions (W x H x D): | 370 x 325 x 151 mm |
| Screen Tilt/Rotate: | -5° to +30°/No |
| Weight: | 4.0 kg |
| Power Supply: | 100–240 V/0.6/0.3 A external AC adapter |
| Power Requirements: | 25 W max. On mode, < 5 W Power saving mode |
| Ambient Temperature (Operat.): | +5 °C to +35 °C |
| Ambient Humidity (Operating): | 30–80 % (non-condensing) |
| Safety/Ergonomics: | CE, TÜV GS, TÜV ERGONOMIE, ISO 9241-3/-7/-8, TCO 99 |
| Warranty: | 3 years warranty, warranty extension programs depending on specific country |
| Shipping Contents: | Monitor, Power cord, VGA signal cable 1.8 m, USB cable, User manual |

All specifications are subject to change without notice. Status February 2000

* CR = Contrast Ratio. All viewing angle specification is based on a contrast ratio of 10:1. Some manufacturers specify viewing angle at a contrast ratio of 5:1 which implies a very pale image.

** Most actual INF file for automatic adaption into Windows 95/98 is downloadable from: www.necd.de

- An allround performer LCD Monitor with analogue input
- New compact design
- VESA mounting interface provides versatile installation
- Ergonomics and safety compliant to state of the art standards



NEC Deutschland GmbH
Steinheilstr. 4–6
85737 Ismaning
Germany

Phone:
+49-89-9 6274-0

Web site:
www.necd.de

NEC
One idea ahead.