

BIOS Release Notes

TITLE

SUBJECT: MZ33-DC0 BIOS Release Notes version F08b
System: MZ33-DC0-000,MZ33-DC1-000,R163-Z30-AAB1-000,
R163-Z30-AAG1-000,R163-Z30-AAB2-000,R163-Z30-AAG2-000,
R163-Z32-AAB1-000,R163-Z32-AAG1-000,R163-Z32-AAC1-000,
R163-Z32-AAH1-000,R163-Z32-AAC2-000,R163-Z32-AAH2-000,
E163-Z30-AAB1-000,E163-Z30-AAG1-000,R263-Z30-AAC1-000,
R263-Z30-AAH1-000,R263-Z30-AAC2-000,R263-Z30-AAH2-000,
R263-Z32-AAC1-000,R263-Z32-AAD1-000,R263-Z32-AAH1-000,
R263-Z32-AAV1-000,E263-Z30-AAD1-000,E263-Z30-AAV1-000,
R163-Z35-AAC1-000,R163-Z35-AAH1-000,R263-Z34-AAC1-000,
R263-Z34-AAH1-000,R263-Z36-AAD1-000,R263-Z36-AAV1-000,
R263-Z36-AAE1-000,R263-Z36-AAJ1-000,R263-Z37-AAC1-000,
R263-Z37-AAH1-000

About This Release

Build Date: 2023/05/31
BIOS Checksum: 0xBF9435F8 (32M)
Release Owner: Candy.Wu

BIOS Components/Contents

Processor stepping(s) supported: AMD Genoa Processors
System hardware configurations supported: MZ33-DC0-000, MZ33-DC1-000
PCB Version:
Microcode updates versions:

| CPUID | Family | Microcode Update ID |
|------------|-------------------------|---------------------|
| Genoa B0 | Family 19h Model 10-1Fh | 0x0A101020 |
| Genoa B1 | Family 19h Model 10-1Fh | 0x0A101135 |
| Genoa B2 | Family 19h Model 10-1Fh | 0x0A101235 |
| Bergamo A0 | Family 19h Model 10-1Fh | 0x0AA00009 |
| Bergamo A1 | Family 19h Model 10-1Fh | 0x0AA00112 |
| Bergamo A2 | Family 19h Model 10-1Fh | 0x0AA0020 E |

IPMI support:
AMI Kernel version: 5.27_GenoaCrb_0ACQT020
AGESA PI version: GenoaPI 1.0.0.7_Patch_Update
OPROM version:

| OPROM | Version |
|---------|---------|
| AST2600 | 1.12.00 |

BIOS Release Notes

Installation Notes

IMPORTANT NOTES:

1. Please extract the MZ33-DC0_F08b.zip to a bootable diskette that use FAT/FAT32 format

BIOS UPDATE INSTRUCTIONS FOR EFI Shell:

1. Insert USB flash drive to system for BIOS upgrade.
2. Power on system and boot to Build-In Shell.
3. Enter your USB filesystem, like "fs0:" or "fsx:", "x" is your USB filesystem number
4. Execute F.nsh for bios update
5. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE INSTRUCTIONS FOR Windows:

1. Insert bios update USB flash drive.
2. Use Command Shell.
3. Enter \Tool\Win32 and execute f.bat for Windows 32bit.
Or
Enter \Tool\Win64 and execute f.bat for Windows 64bit.
4. After bios flash finish, system must Power-Off to have the changes take effect.

BIOS UPDATE FOR Easy BIOS Refresh:

1. The system supports remotely update BIOS if BMC existent.
2. Please download the Easy BIOS Refresh User Guide from Gigabyte website, target system support page.

BIOS Version CHECK INSTRUCTIONS:

1. Power on system and press during POST
2. The bios version shows on the first main page

Known Issues/Workarounds

Issues fixed in this version

F08b

1. Support GenoaPI-SP5 1007 Patch.
2. Added R263-Z36-AAD1-000,R263-Z36-AAV1-000,R263-Z36-AAE1-000,R263-Z36-AAJ1-000,R263-Z37-AAC1-000,R263-Z37-AAH1-000 system support.
3. Optimize Hotplug compatibility.

F08a

1. Updated AGESA 1.0.0.7.

F07

1. Update Inventory Mapping system.

BIOS Release Notes

2. Fixed COM Port mouse is not working.
 3. Added DIMM Manufacturer ID 0x1A08.
 4. Fixed NVME LED control failed.
 5. Fixed SATA LED Control failed.
 6. Adjust the display order of NVME devices list.
 7. Added R163-Z35-AAC1-000, R163-Z35-AAH1-000, R263-Z34-AAC1-000, R263-Z34-AAH1-000 systems support.
-

F06

1. Updated AGESA 1.0.0.5.
 2. Fixed SATA incorrect issue on WebUI page.
-

F05

1. Added system R163-Z30-AAG1-000, R163-Z30-AAG2-000, R163-Z32-AAG1-000, R163-Z32-AAH1-000, R163-Z32-AAH2-000, E163-Z30-AAG1-000, R263-Z30-AAH1-000, R263-Z30-AAH2-000, R263-Z32-AAD1-000, R263-Z32-AAV1-000, E263-Z30-AAV1-000 support.
-

F04

1. fixed sata hot plug function.
-

F03

1. Fine tune memory slot naming.
-

F02

1. Update AGESA 1.0.0.2.
 2. Update Microcode.
 3. Support Bergamo CPU.
-

F01

1. First release.
-